

DATA SHEET

PORTA


soni PORTA | soni PORTA Basic

- ▶ Our **soni PORTA** kit consists of six precision-fit elements that form an attractive pattern and are directly glued to the door so that they achieve an optimum their sound-insulating and sound-damping effect. Thanks to our unique, **newly developed self-adhesive solution**, you can remove **soni PORTA** again from smooth surfaces **without any residue**, if necessary, for instance when moving out.
- ▶ **soni PORTA** is suitable for any room door, for instance in day-care centers, kindergartens, schools, medical facilities, offices, hotels, banks, etc.
Please pay attention to compliance with fire protection classes, if applicable.



TECHNICAL DATA

FLAMMABILITY	<ul style="list-style-type: none"> ▶ Fulfills the strict fire safety standard for the automotive industry (FMVSS 302, DIN 75 200) ▶ ISO 3795, burning rate < 100 mm/min
COLOR FASTNESS TEST OF FELT COVER	▶ DIN EN ISO 105-B02: 6-7
ABRASION RESISTANCE OF FELT COVER	▶ ISO 12947-2: > 50.000 rubs
COLOR	<ul style="list-style-type: none"> ▶ Orange ▶ Green ▶ Beige ▶ Blue ▶ Light grey ▶ Pink ▶ Anthracite ▶ Red ▶ Greige



Directly to the product | Color selection

DIMENSIONS

THICKNESS [mm]	INSTALLATION AIDS* [mm]	MEASUREMENT OF THE DOOR LEAF 860 X 1985 mm	MEASUREMENT OF THE DOOR LEAF 985 X 1985 mm
52	10	PORTA IN: 800 X 1955 Weight: 7.9 kg PORTA OUT: 855 X 1975 Weight: 8.6 kg	PORTA IN: 925 X 1955 Weight: 9.2 kg PORTA OUT: 980 X 1975 Weight: 9.9 kg

*Included in the scope of delivery

ADVICE

- ▶ There might be minimal color variations between different lots, which will not constitute a reason for complaint.
- ▶ Please refer to the "Cleaning the adhesive substrate" section of our processing and storage instructions.
- ▶ soni PORTA Basic cannot be removed without leaving a residue.


BENEFITS

- ▶ Easy installation with installation aid and clear instructions
- ▶ Residue-free removal from smooth surfaces
- ▶ Good noise absorption capacity. Noise reduction by **3 dB***
- ▶ Felt surface is robust, abrasion-resistant and dirt-repellent
- ▶ Edges can be masked with our soni VLD adhesive tape if desired

* Official measurement in an institute for door test stands


SOUND TRANSMISSION LOSS

▶ DIN EN ISO 10140-2



APPLICATIONS

- ▶ Earsplittingly loud music from your teenager's room, bothersome noise from the hallway, loud phone conversations from the adjacent office, lack of discretion in treatment rooms - wherever closed doors are supposed to provide undisturbed quiet, our door insulation kit is the ideal solution for effective noise reduction.
- ▶ Advice: The door insulation kit has to be installed always on the side of the noise source.



PORTA

PLEASE SEE OUR PROCESSING AND STORAGE INSTRUCTIONS

Details and values given in this leaflet are average values and have been compiled with care. They are not binding, however, and Cellofoam International GmbH & Co. KG disclaims any liability for any damages and detriments, also in connection with any third party's rights. The information given does not release the buyers from making the necessary experiments and tests themselves. Subject to technical changes. For updates please go to our website.

Cellofoam International GmbH & Co. KG
 Business unit soniflex
 P: +49 7351 340 28 61
 sales@soniflex.de / www.soniflex.de

VERSION 06/24

Distribution partner for Switzerland:
 soniflex Switzerland
 P: +41 44 377 60 50
 einkauf@soniflex.ch / www.soniflex.ch